


Aluminium ANODE K4-2

gross weight: 6,00 kg
nett weight: 5,30 kg



Technical specification AlZnIn - alloy type A2 according to EN12496:2013 :

Alloying elements:		Impurities:	
Zn [%]:	3,0 - 5,5	Fe [%]:	max 0,09
In [%]:	0,016 - 0,040	Cu [%]:	max 0,005
Al -	balance	Si [%]:	max 0,10

Electrochemical efficiency min: 2500 Ah/kg
according to DNV RP B401 test appendix B

Note:

- All weights and dimensions are nominal.
- Dimensions in mm

 MAKROMOR CATHODIC PROTECTION	MAKROMOR SP. Z O.O. Ul. Gołębia 15 81-185 Gdynia, POLAND Phone: +48 58 661-57-99 Fax: +48 58 661-01-89 e-mail: biuro@makromor.pl website: www.makromor.pl		Scale:	1:5
			Insert type:	S235JR
		Alloy:		AlZnIn
Type:		Alternative type:		
ALUMINIUM HULL ANODE K4-2				
Product code:		Drawing No.:		
A60/K4/100/50/500/580/0		AK42/0		
Drawer:	Date:	Approved:	Date:	
Ewa Nawrocka	16-04-2013	Grzegorz Prytowski	17-04-2013	
Copyright MAKROMOR SP. Z O.O. All rights reserved.				